

ADS

Automatic Static Storage Heater



Technical features

- ▶ Designed to use Off-Peak electricity.
- ▶ Automatic damper control.
- ▶ Safety thermostat with manual reset.
- ▶ Discharge thermostatic regulator. In the ADS-84 this regulation is automatic, not including the discharge control.
- ▶ Charging thermostat with DUAL SENSOR tube.
- ▶ Reinforced double rear insulation to avoid losses to the outside of the house.
- ▶ Microtherm G 12 mm insulation, vermiculite and ecological fiber.
- ▶ Side, front and rear air chambers.
- ▶ High resistance polyamide floor fitting supports.
- ▶ Powder coated RAL 9010 steel structure.

MODEL		ADS-84	ADS-124	ADS-168	ADS-208	ADS-2412	ADS-2812	ADS-3216
Output 230 V / 240 V	W	800 / 871	1200 / 1307	1600 / 1742	2000 / 2178	2400 2613	2800 / 3049	3200 / 3484
Accumulated energy	kWh	6.4	9.6	12.8	16	19.2	22.4	25.6
Length	cm	31.5	43	54.5	66	77	89	99.5
Width*	cm	16.5	16.5	16.5	16.5	16.5	16.5	16.5
Height	cm	73	73	73	73	73	73	73
Total weight	kg	48	69	88	109	129	150	169
Number of Blocks 8.5kg		4	-	8	4	12	8	16
Number of Blocks 12.65kg		-	4	-	4	-	4	-
Frequency	Hz	50-60	50-60	50-60	50-60	50-60	50-60	50-60
Units per pallet		24	12	12	12	24	12	12
EAN 13		8432336200601	8432336200625	8432336200649	8432336200663	8432336200687	8432336200700	8432336200724

*Plus 2cm space from the wall