

# PH & PHT

## Panel Heaters



### Technical features

- ▶ Power range from 750W to 2000W.
- ▶ Two power options on all the models with the exception of PH-075 and PH-075T.
- ▶ Frost protection mode.
- ▶ Daily programmer in PHT models.
- ▶ Built-in ambient thermostat  $\pm 0,5^{\circ}\text{C}$ .
- ▶ Thermal safety cut out.
- ▶ Switch indicator of consumption.
- ▶ Protection IP 24, splash proof.
- ▶ Class I insulation.
- ▶ Controls protection cover made in polycarbonate.
- ▶ Powder coated RAL 9010 steel structure.
- ▶ Fitted with 1,5 m mains cable.
- ▶ Unique wall fixing brackets included.
- ▶ Compatible with standard power managers as RG90, offered as accessory.
- ▶ Compatible with wireless energy saver for windows.

## PH

MODEL		PH-075	PH-125	PH-150	PH-200
Input	W	750	1250 (500+750)	1500 (750+750)	2000 (1000+1000)
Current	A	3.3	5.4	6.5	8.7
Voltage	V	230-240	230-240	230-240	230-240
Frequency	Hz	50-60	50-60	50-60	50-60
*Dimensions	cm	41x41x10.5	56x41x10.5	63x41x10.5	78x41x10.5
Net weight	kg	4	5	6	7
**Units per pallet		72	48	36	36
EAN 13		8432336601453	8432336601552	8432336601651	8432336601750

\*2.5 cm space from wall.

\*\*Three units per packaging. Internal individual protective carton included.

## PHT

MODEL		PH-075T	PH-125T	PH-150T	PH-200T
		Manual switch on/off, 24 hours programmer			
Input	W	750	1250 (500+750)	1500 (750+750)	2000 (1000+1000)
Current	A	3.3	5.4	6.5	8.7
Voltage	V	230-240	230-240	230-240	230-240
Frequency	Hz	50-60	50-60	50-60	50-60
*Dimensions	cm	41x41x10.5	56x41x10.5	63x41x10.5	78x41x10.5
Net weight	kg	4	5	6	7
**Units per pallet		72	48	36	36
EAN 13		8432336601859	8432336601958	8432336602054	8432336602153

\*2.5 cm space from wall.

\*\*Three units per packaging. Internal individual protective carton included.