

PHM & PHMT

Panel Heaters



Technical features

- ▶ Input from 750W to 2000W.
- ▶ Frost protection mode.
- ▶ Built-in ambient thermostat.
- ▶ Daily programmer in PHMT models.
- ▶ Thermal safety cut out.
- ▶ Switch indicator of consumption.
- ▶ Protection IP2X.
- ▶ Class I insulation.
- ▶ Powder coated RAL 9010 steel structure.
- ▶ Fitted with 1,5m mains cable.
- ▶ Unique wall fixing brackets included.
- ▶ Compatible with standard power managers as RG90, offered as accessory
- ▶ Compatible with wireless energy saver for windows.

PHM

MODEL		PHM-075	PHM-125	PHM-150	PHM-200
Output	W	750	1250	1500	2000
Current	A	3.3	5.4	6.5	8.7
Voltage	V	230-240	230-240 V	230-240 V	230-240 V
Frequency	Hz	50-60	50-60	50-60	50-60
*Dimensions	cm	41x41x10.5	56x41x10.5	63x41x10.5	78x41x10.5
Net weight	kg	3.5	4	4.5	5.5
**Units per pallet		72	48	36	36
EAN 13		8432336601422	8432336601521	8432336601620	8432336601729

*2.5 cm space from wall.
**Three units per packaging. Internal individual protective carton included.

PHMT

MODEL		PHM-075T	PHM-125T	PHM-150T	PHM-200T
			Manual switch on/off, 24 hours programmer		
Output	W	750	1250	1500	2000
Current	A	3.3	5.4	6.5	8.7
Voltage	V	230-240	230-240	230-240	230-240
Frequency	Hz	50-60	50-60	50-60	50-60
*Dimensions	cm	41x41x10.5	56x41x10.5	63x41x10.5	78x41x10.5
Net weight	kg	3.5	4	4.5	5.5
**Units per pallet		72	48	36	36
EAN 13		8432336601330	8432336601354	8432336601378	8432336601392

*2.5 cm space from wall.
**Three units per packaging. Internal individual protective carton included.