

SH-M

Manual Static Storage Heater



Technical features

- ▶ Designed to use Off-Peak electricity.
- ▶ Grille painted in a heat resistant colour.
- ▶ Damper control device.
- ▶ Safety thermostat with manual reset.
- ▶ Class I insulation.
- ▶ Discharge thermostatic regulator. In the SH6-M this regulation is automatic, not including the discharge control.
- ▶ Charging thermostat with phial.
- ▶ Microtherm G 10 mm insulation, vermiculite and ecological fibre.
- ▶ Side, front and rear air chambers.
- ▶ High density storage blocks.
- ▶ Ultra slim, only 15 cm.
- ▶ High resistance polyamide floor fitting supports.
- ▶ Powder coated RAL 9010 steel structure.

MODEL		SH6-M	SH9-M	SH12-M	SH15-M	SH18-M	SH24-M
Output 230 V / 240 V	W	800 / 871	1200 / 1307	1600 / 1742	2000 / 2178	2400 / 2613	3200 / 3484
Accumulated energy	kWh	6.4	9.6	12.8	16	19.2	25.6
Length	cm	31.5	43	54	65	76.5	99
Width*	cm	15	15	15	15	15	15
Height	cm	72.5	72.5	72.5	72.5	72.5	72.5
Total weight	kg	43	61	79	98	116	152
Number of Blocks 7.5 kg		4	-	8	4	12	16
Number of Blocks 11 kg		-	4	-	4		
Frequency	Hz	50-60	50-60	50-60	50-60	50-60	50-60
Units per pallet		24	24	24	12	12	12
EAN 13		8432336105104	8432336105203	8432336105302	8432336105402	8432336105500	8432336105708

*Plus 2cm space from the wall