

RG-CPL

ENERGY MANAGER SUITABLE FOR MAINS BORNE SIGNALLING, SINGLE AND THREE PHASES



Power manager appropriate for heaters monitored with mains borne signaling control units, CPL, with individual receptors. This manager does not require receptors' interconnection.

Technical Features

- ▶ Gestión centralizada de toda la instalación, sin cables, a través de corrientes portadoras (CPL)
- ▶ Incluido un transformador de intensidad TI 2/90 A.
- ▶ Para instalaciones trifásicas añadir otros dos TI 2/90 A.
- ▶ ADF acoplador de fases para instalaciones trifásicas.

Suitable for:

- Thermal inertia radiators RKHi, RKL, RKSHi y RKSL.

MODELO	RG-CPL	
Input		4VA
Voltage		230V~
Communication protocol		X2D
DHW output		2A
Insulation		Clase II
Installation		Carril DIN 35
Width		4 módulos de 18 mm
Approvals		CE , CENELEC, NF
Dimensions	cm	7x8.4x6
Weight	kg	0.3
Dimensions with packaging	cm	11x6.5x4
Gross weight	kg	0.5
EAN13		8432336610226

TI 2/90 A, offered as an accessory.

ADF phase coupler, offered as an accessory.